

TAX METER TM: THE MOST EFFICIENT AND SECURE WAY TO COLLECT STAMP DUTY

Secure – fast – reliable. The Frama Tax Meter TM with LAN Ethernet connection provides access to all modern ways of stamp duty collection. A well thought through solution.





Secure printing technology

The dual colour digital print protection (thermal-transfer) uses fluorescent ink against copying and blue ink for barcode verification via scanning devices.



Feed Control

No misprinting possible. Protection of money is 100% guaranteed. Easy and convenient single sheet printing.

Benefits

- Large touchscreen – easy to operate
- Pre-set values – OneTouch for the most used stamp values
- Large print table – easy and convenient single sheet printing
- Fast printing speed – saves you time
- Feed Control – 100% money protection
- Automatic date change – convenience
- Standard: Stable, secure connections to the server via the Internet (LAN Ethernet) no bottlenecks for upgrading the rates or receiving new funds or updates
- Option: Manual loading solution available – works without external servers
- Highest security standards – ideal for your process security: Remote inspection (for Data Centre operation only), password protection, non-resettable counters, special lock with lead seal



Stay connected

The Tax Meter TM comes with LAN Ethernet connection for the integration in your corporate network. Select between a wireless or cable-based network setup for guaranteed, stable and secure connections.

Touchscreen

The patented touchscreen with OneTouch functionality makes the operation child's play. Fast, simple determination of the stamp duty amount – without charts, codes and operating instructions! Touch – print.



Technical data

- Speed: up to 3000 prints / hour
- Max paper thickness: 6mm
- Printing technology: Smear free thermotransfer technology
- OneTouch Keys: up to 9
- Manual keyboard
- Cost centres: up to 50
- Automatic date setting with server synchronisation
- Housing colour: Anthracite
- Loudness: 54db(A)

Power consumption

- Off: 0 W
- Ready to frank: 6.8 W
- In operation: 36 W

Dimension / Weight

- Weight: 6 kg

